




Main features

- Through pickling of models in precious metals.
- Use of environment-friendly ecological products
- Pickling bath constantly maintained at the operating temperature.
- Maximum convenience and safety, with no need for extractor hoods or protective masks.
- Complies in full with current legal requirements.

 [Download this page in PDF format](#)

 [Print this page](#)

other products

products

Pickling tanks



Pickling, in which items are generally dipped in an acid solution, is a procedure used to remove the film of black oxidation which forms on the surface of metals after high temperature casting. When processing precious metals, this in-depth cleansing operation must be carried out with the greatest delicacy.

The pickling tanks, available in models of 1.5E - 3.5E and 10,5E litres, are ideal for pickling operations in the processing of precious metals in conditions of maximum safety. Constructed in stainless steel, they are suitable for use with ecological product in accordance with current legal requirements. This means there is no need for an extraction hood or protective masks for the operators. The pickling tanks are equipped with a basket, also in stainless steel, in which the objects are placed and then dipped in the tank of pickling solution. The bath is heated by a thermostatically controlled element with fixed temperature setting (65°C), except for the model 10,5E, which has an adjustable thermostat with range 0 to 90°C, ensuring that the appliance is always ready for use.



1 E		width	depth	height
external dimensions	mm	195	180	210
usable tank dimensions	mm	155	140	120
tank capacity	lt	1		
power supply voltage	V	220	50/60Hz	
heating power	W	100		

3,5 E		width	depth	height
external dimensions	mm	280	175	210

[Click here](#)
for having an offer
of our products



Download Acrobat Reader to read PDF files

usable tank dimensions	mm	240	140	120
tank capacity	lt	3,5		
power supply voltage	V	220	50/60Hz	
heating power	W	160		

10,5 E

		width	depth	height
external dimensions	mm	415	280	290
usable tank dimensions	mm	300	240	170
tank capacity	lt	10,5		
power supply voltage	V	220	50/60Hz	
heating power	W	500		



Print this page

all rights reserved to Logimec srl - s.s.solero, 19 - zona ind. D/4 - 15048 Valenza (AL)
Tel. +39 0131 946 404 - Fax +39 0131 955 691 - email: info@logimec.net

Designed by Digitalrule - Hosted by Ubimajor